

RACK MOUNT MEGA TITAN-48UPS



Introducing the Rack Mount Mega Titan -48V UPS! Designed for 19" rack mount installations. The Rack Mount Mega TITAN provides a continuous -48V of UPS power including ONT dry contact alarms placed on a CAT-5 connection for easy field termination. Our field proven battery management system ensures long life and reliable power in harsh environments.

•-48V @ 150W

- •10 Year design-life GS Battery.
- •10 to 12-hour runtime with typical 150W rated ONTs.
- •Automatic 45-day battery testing.
- •Temp compensated battery charging.
- •2 RU space requirement
- •Designed and Manufactured in the USA!





RACK MOUNT MEGA TITAN-48



Input

AC Input Voltage AC Input Frequency Plug Type Cable Length 90V - 305Vac 47/63 Hz 3 prong grounded 14'

150 watts

48V

DC Output

Power Voltage Connector Alarms

Battery Type Model Capacity Lead acid GS Battery PYL12V80TT 80Ah

Battery Fail, Battery Missing

2 position screw terminal On Battery, Battery Low

Physical

2 RU Dimensions Weight Power Cable Alarms Mounting Options

3.5" H x 19"W x 11.5"D (in./approx) 10lbs. (without Battery) 12AWG Cat-5 connection 19" Rack

FCC 47 CFR Part 15 Class B

Environment

Operating Temperature-40°C to +55°C (-40°F to + 131°F)Operating Humidity0% to 95% non condensing

Safety Compliance

Emissions:

5 years

Bold indicates industry-best



Specifications subject to change without notice

630 Lincoln Ave., Clay Center, KS 67432 • 877-799-3774 • www.espicorp.com

© 2022 ESPi. All Rights Reserved. All trademarks mentioned are property of their owners.