

**TITAN** Outdoor



The TITAN Outdoor uninterruptible power supply for FTTh – “your next generation UPS” – is the most technologically advanced FTTh UPS in the world today. Designed for performance, durability, reliability, and ease of service, the TITAN outdoor has the lowest TCO in the industry. Our 8Ah battery sets a new standard for FTTh UPS, delivering more standby power thanks to our new ThermoAmp Technology. Our advanced on board firmware calibrates voltage to the battery according to ambient temperature fluctuations, charging the battery precisely and accurately and thus extending its life. The TITAN Outdoor UPS™ also has numerous design features for flexible installation, ease of service, and fewer service calls. Add up the TITAN Outdoor benefits; higher performance, longer life, and service optimization, and the result is the industry’s lowest lifetime cost for FTTh UPS.

- Save up to 50% of UPS operating expense
- Up to 14 hours of ONT runtime
- 6-8 year battery design life
- Advanced Thermo-Amp technology for precise temperature-compensated charging to extend battery life
- Advanced diagnostics algorithm for accurate determination of battery status
- Modular components for easier service, including swappable fuse and electronics
- Telecommunications grade UPS for FTTh, wireless, other broadband applications
- Field-ready design: AC-DC conversion at the outlet, up to 115’ power cable for flexible installation
- Industry-first alarm wire connector for ease of installation and guaranteed visual wire connections = 30% time savings over conventional screw terminal connectors
- Warranties: 6 years battery (4 full, 2 prorated) – industry-best. 3 years electronics



<b>Input</b>	
AC Input Voltage	<b>120Vac</b>
AC Input Frequency	<b>50/60 Hz</b>
Plug Type	2 prong ungrounded

<b>Output</b>	
Output Power, Operational	<b>30W max. continuous (ONT load)</b>
Output Voltage	<b>12-14.5Vdc Nominal</b>
Output Connector	2 Position Screw Terminal
Alarm Output	<ul style="list-style-type: none"> <li>• On Battery • Battery Low</li> <li>• Battery Fail • Battery Missing</li> </ul>

<b>Battery</b>	
Type	<b>8Ah lead acid, maintenance-free, leak-proof</b>
Design Lifespan	<b>8 years</b>
Runtime	<b>Up to 14 hours</b>

<b>Battery charging circuit</b>	
Type	<b>Advanced Firmware with Temperature Compensated Charging</b>

<b>Thermo-Amp Technology</b>	
Precise charging	<b>Based on ambient temperature providing maximum battery lifespan</b>
Load Testing	<b>Advanced auto-test algorithm</b>
Frequency	<b>45 days</b>

<b>Diagnostics: System LED</b>	
Green	Normal status: commercial power available
Green Flashing	Battery is in Test Mode
Yellow Flashing	Input not present, battery discharging
	> 1 per second > 66% battery
	> 2 per second 33%-66% battery
	> 3 per second < 33% battery
Red	Replace battery: failed self-test
Red Flashing	Battery missing
Red - Yellow	Temperature above +150°F
All three flashing	<b>Short-circuit between UPS and ONT</b>

<b>Physical</b>	
Unit Dimensions	TITAN - 8.5H x 8.5W x 4D (in./approx)
Unit Weight	7.6 lb. / 3.4 kg (with battery)
AC/DC Converter	At AC outlet
Power Cable	16 gauge up to 115 ft long for mounting flexibility
Alarms	Connector allows for visual verification of connected wires
Modular Design	Swappable circuit board, fuse, battery
Mounting Options	Wall or Pole Mountable

<b>Environment</b>	
Operating Temperature Electronics	<b>-40°C to +65°C ( -40°F to + 149°F)</b>
Operating Temperature Battery	<b>-40°C to +65°C ( -40°F to + 149°F)</b>
Operating Humidity	0% to 95%

<b>Safety compliance</b>	
System:	Safety: UL60950-1 2nd edition Emissions: FCC 47 CFR Part 15 Class B

<b>Warranties</b>	
Electronics	3 Years
Battery	<b>6 Years - 4 years full + 2 prorated</b>

*\*Bold indicates industry-best*

