




KEEPING YOU CONNECTED



## Key Benefits

- Multi-Output Design: Extends network power for ONT and Gateway with a single unit.
- Backup Time: ONT + Gateway: 3–5 hours
- Gateway Only: 6-10 hours with sleek, modern in-home design.
- Enhanced Customer Experience
- 911 Emergency Calling: Provides uninterrupted access to emergency services through Wi-Fi calls.
- Security and Peace of Mind: Ensures Wi-Fi remains operational during power outages.
- Versatile Applications: Powers PoE devices, including ONTs and video surveillance equipment.
- Portable Power Bank: Acts as a large-capacity backup for additional needs.

## Business Advantages for ISPs

- Boost Customer Satisfaction: Keep customers connected during power outages and brownouts and reduce churn rates.
- Drive Revenue Growth: Offer the Wi-Fi UPS as part of a top-tier package or charge a nominal monthly fee.
- Stand Out in a Crowded Market: Use as a powerful marketing tool to attract new customers and build loyalty.

## Why Choose the Wi-Fi UPS PLUS?

- Innovative Power Solutions: Designed for flexibility and reliability.
- Customer-Centric Features: Tailored to meet the evolving needs of modern households and smart home devices.
- Market Differentiator: Elevates your service offerings and strengthens your brand.



Your Next Generation UPS

#### Input

AC Input Voltage	100-240V
AC Input Frequency	50/60 Hz
Plug Type	2 prong ungrounded

#### Output

Output Power: 60W  
 POE Output Voltage and Current: 48V/.89A  
 DC Output Voltage and Current: 12V/3A total  
 USB-A Output Voltage and Current: 5V/2.5A  
 USB-C 5V/3A and 9V/2A  
 DC Output Size: Female DC 5.5\*2.5mm

#### Battery

Type : Li-ion 76.96Wh/20800 mAh  
 Design Lifespan 8 years  
 Runtime Up to 8 hours

#### Physical

Product size: 7" x 6.1" x 1.6"  
 Net weight: 1.9 lbs

#### Environment

Operating Temperature Electronics 0°C to +50°C ( 32°F to + 122°F)


Operating Humidity 0% to 95%




#### Safety compliance:



\*Includes 2 adapters, 1 AC Power Cable, 2 DC Cables



1. Ethernet LAN in port
2. POE output port
3. 12V output port
4. 12 V output port
5. AC power input socket



1. USB C
2. USB A
3. Working status indicator
4. On/Off switch
5. 100% battery capacity indicator
6. 75% battery capacity indicator
7. 50% battery capacity indicator
8. 25% battery capacity indicator