



## Key Benefits

- Multi-Output Design: Extends network power for ONT and Gateway with a single unit.
- Backup Time: ONT + Gateway: 3-5 hours
- Gateway Only: 6-10 hours with sleek, modern in-home design.
- Enhanced Customer Experience
- 911 Emergency Calling: Provides uninterrupted access to emergency services through Wi-Fi calls.
- Security and Peace of Mind: Ensures Wi-Fi remains operational during power outages.
- Versatile Applications: Powers PoE devices, including ONTs and video surveillance equipment.
- Portable Power Bank: Acts as a large-capacity backup for additional needs.

## Business Advantages for ISPs

- Boost Customer Satisfaction: Keep customers connected during power outages and brownouts and reduce churn rates.
- Drive Revenue Growth: Offer the Wi-Fi UPS Lite as part of a top-tier package or charge a nominal monthly fee.
- Stand Out in a Crowded Market: Use as a powerful marketing tool to attract new customers and build loyalty.

## Why Choose the Wi-Fi UPS Lite?

- Innovative Power Solutions: Designed for flexibility and reliability.
- Customer-Centric Features: Tailored to meet the evolving needs of modern households.
- Market Differentiator: Elevates your service offerings and strengthens your brand.





Your Next Generation UPS

<b>Input</b>	
AC Input Voltage	100-240V
AC Input Frequency	50/60 Hz
Plug Type	2 prong ungrounded

<b>Output</b>	
Output Power: 30W POE Output Voltage and Current: 24V/1A, 48V/0.5A	
DC Output Voltage and Current: 12V/2A, 12V/2A	
USB Output Voltage and Current: 5V/2.5A	
DC Output Size: Female DC 5.5*2.5mm	

<b>Battery</b>	
Type: Li-ion	76.96Wh/20800 mAh
Design Lifespan	8 years
Runtime	Up to 8 hours

<b>Physical</b>	
Product size: 7.7" x 4.5" x 1"	
Net weight: 1.9 lbs	

<b>Environment</b>	
Operating Temperature Electronics	0°C to +50°C (32°F to +122°F)
Operating Humidity	0% to 95%



\*Includes 2 adapters, 1 AC Power Cable, 2 DC Cables

Safety compliance:



- |                                    |                                  |
|------------------------------------|----------------------------------|
| 1. Working status indicator        | 7. POE output port               |
| 2. ON/OFF switch                   | 8. Ethernet LAN in port          |
| 3. 100% battery capacity indicator | 9. POE port output volt selector |
| 4. 75% battery capacity indicator  | 10. USB 5V output port           |
| 5. 50% battery capacity indicator  | 11. DC 12V output port           |
| 6. 25% battery capacity indicator  | 12. DC 12V output port           |
|                                    | 13. AC power input sockets       |



630 Lincoln Ave., Clay Center, KS 67432 • 877-799-3774 • www.espicorp.com